THE CONTRACTOR SHALL PERFORM APPLICABLE CONSTRUCTION WORK IN ACCORDANCE WITH THE PLANES AND PROLECT SPECIFICATIONS WHEN WORK ON APPLICABLE CONSTRUCTION SHAPE. AND PROLECT SPECIFICATIONS WHEN CONTRACTOR SHALL PERFORM WORK ON ACCORDANCE WITH THE STANDARD STRADE DETAILS. FOR PUBLIC WORKS CONSTRUCTION CITY AND COUNTY OF HONOLULLI. ACTO SEPTIMER 1984 AS MALERICET, THE STANDARD SEPTIMENT OF HOR THE PERSON HORSES CONSTRUCTION WATER STANDARD SEPTIMENT OF PUBLIC WORKS, OTT AND COUNTY OF HONOLULLI. AND THE RECYCLED MORNINGES OF HONOLULLI. 1990, AS AMENDED. WATER UTILITY CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE WATER STEEL STANDARDS. COTT AND COUNTY OF HONOLULLI 2002 AS ALL DEMOLITION WORK SHALL BE CONFINED WITHIN THE LIMITS SHOWN. THE LINGERGOUND PIESE, CABLES OR DUCTINES KNOWN TO ENST BY THE DEMONETS FROM HIS RESEARCH OF RECORDS ARE MODIFIED ON HER PLANS. THE CONTRACTOR SHALL REFEY THE LOCATIONS AND DEPTHS OF THE FAULTIES AND EXPOSE PROPER DATE IN THE CONTRACTOR SHALL REPORT PLANS THE CONTRACTOR SHALL SHOULD AND THE PLANS. THE CONTRACTOR SHALL PURPOSE THE EXISTING LINES AT THE PROPOSED CONNECTIONS OF VEHICLES AND EXPOSE PROPER TO EXCANATION FOR THE NEW LINES. **DEMOLITION NOTES** THE CONTRACTOR SHALL POTHOLE ALONG ALL ASH OR MSW CELL LOCATIONS WHERE GRADING OR EXCAVATION OPERATIONS MAY OCCUP TO VERIFY LINER EDGE PRIOR TO ANY CONSTRUCTION OPERATIONS. THE CONTRACTOR SHALL MANTAIN AND REPAIR ALL EROSION CONTROL MEASURES DURNO, ALL CONSTRUCTION OPERATIONS AND SHALL NISPECT ALL MEASURES AFTER SONIFICANT STORM EVENTS FOR BEREACHES AND/OR DESTRUCTION OF ALL EXISTING MEASURES. THE LOCATION AND DEPTH OF EVISING UNITED METHOD ON NOT THE CONTRACTOR. SHOWN ON THE DAMES SHALL BE VERBELD BY THE CONTRACTOR. SHOWN ON THE DAMES SHALL BE VERBELD BY THE CONTRACTOR. TO THEM SHALL BE REPARED AND PAID FOR SHIPE CONTRACTOR. THE CONTRACTOR SHALL TAKE THE NECESSARY PRECAUTIONS TO PREVENT DAMAGE TO THE EXISTING WALLS: FEREES, BUILDINGS, UTILITIES, AND STRUCTURES OUTSIDE OF THE LIMITS OF DEMOLITION, ANY DAMAGE TO THESE TIEMS SHALL BE REPARED TO EQUAL TO OR BETTER THAN EXISTING CONDITIONS BY THE CONTRACTOR AT THE CONTRACTOR'S EXPENSE. THE CONTRACTOR SHALL BE RESPONSIBLE FOR CONFORMANCE WITH THE APPLICABLE PROVISIONS OF CHAPTER 54, MATER DULLING CONFORD, AND CHAPTER 54, MATER POLITION CONFORD, OF TITLE STANDARDS, AND CHAPTER STANDED DEPARTMENT OF HEALTH. ALL WORK CALLED FOR ON THE PLANS AND NOT TITRIZED IN THE PROPOSAL AND ALL WORK NOT CALLED FOR BUT REQUIRED FOR THE CONSTRUCTION OF THIS PROJECT, SHALL BE CONSIDERED WODERTAL VERIFY AND CHECK ALL DMENSIONS AND DETAILS SHOWN ON THE DRAWNOSS PROPE TO THE START OF CONSTRUCTION. ANY DISCREPANCY SHALL BE IMMEDIATELY BROUGHT TO THE ATTENTION OF THE OWNER'S REPRESENTATIVE FOR CLARIFICATION. SHALL PAY FOR ALL DAWACEST OF THE STREET CONTROLLES AND STREET CON GENERAL NOTES WHEN TRENCH EXCAMTION IS ADJACED TO DE WINDER EXISTING STRUCTURES. OHE PACULTIES, THE CONTRACTOR SALAL LE RESPONSIBLE TOP REPORTEY SHEETING AND BRACHOUTHE EXCAMTION AND STABILLING THE EXISTING GROUND TO REDIDER IT SAFE AND SECURE FROM POSSIBLE SIDES. CAVIC-INS AND SETTILLATOR, AND FOR HEAVY, STRUTS OR UNDERPINANTO TO FULL PROTECT IT FROM HEAVY, STRUTS OR UNDERPINANTO TO FULL PROTECT IT FROM AERIAL TOPOGRAPHIO SURVEY MAS PREPARED DIN JUNE 12, 2005 BENCHMARKS USED WERE BASED ON THE FOLLOWING CONTROLS. AZMJUTHS JAND COORDINATES REFERENCED TO THE HAMPUT STATE PLANE PILE NO. : 88119-JOEN-NOTES: DESCRIBE SWF DRAWN: 'RKH OHEOGED; FEB. APPROVED: ---88119 Ч 10. THE CONTRACTOR'S ATTENTION IS DIRECTED TO CHAPTER 42 "VEHICULAR NOISE CONTROL, FOR SOHU," AND CHAPTER 45 "COMMUNITY NOISE CONTROL, FOR SOHU," AND CHAPTER 45 "COMMUNITY NOISE CONTROL, FOR SOHU," AND CHAPTER 45 "COMMUNITY NOISE CONTROL, FOR SOHU, THE FULLS, PROFESSIONAL ENGINEER ACGRECATE BASE ROAD AND TRENCH BACKFILL SHALL CONFORM TO STATE OF HAWAII STANDARD SPECIFICATIONS SECTION 304. HAUL ROAD ACGRECATE BASE COURSE SHALL BE 2-1/2" SIZE. RECOMMENDED BY THE OWNER OR OWNER'S REPRESENTATIVE. HANCOR FLARED END SECTION (FES) SHALL BE HDPE 15" OR 24" AS INDICATED ON PLANS. HANCOR HIGH DENSITY PONYETHYLINE (HOPE) PIPE CORRUGATED PLASTIC PIPE (1979) SHALL BE THERE SHOLE WALL WHEN INSTALLED WALL WHEN INSTALLED WALL WHEN INSTALLED WALL WHEN TERROPED UNDER ROADS, UNLESS OFFERWISE MODIFIED ON THE PLANS. THE CONTRACTOR SHALL OBTAIN AND PAY FOR ALL PERMITS AND ICENSES REQUIRED. THE CONTRACTOR SHALL CONDOCT ALL TESTS AS REQUIRED BY THE CONMERS REPRESENTATIVE AND BE RESPONSIBLE FOR ALL EXPENSES INCURRED IN CONDUCTING THESE THE CONTRACTOR SHALL IMMEDIATELY NOTIFY THE CONNER'S REPRESENTATIVE AND THE STATE HISTORIC PRESERVATION OFFICE UPDN UNCOVERING ANY POTENTIAL HISTORICAL ARTIFACTS OR ITEMS OF MECHAEOLOGICAL SIGNIFICANCE. THE COMPACTOR SYMLL BE RESPONSIBLE FOR COMPRIMANCE WITH THE APPLICABLE PROVISONS OF THE WARER QUALITY AND WATER POLLUTION CONTROL. STANDARDS COMMINED IN HAWAI ADMINISTRATIC RULES, CHAPTER 31–54. "WATER POLLUTION CONTROL." AS WELL AS CHAPTER 14 OF THE REVISED REQUIRANCES OF MOROCULA SAMENDED. BEST MANAGERINI PROCINCES SYALL BE EMPLOYED AT ALL TWEST DIFFRIC CONSTRUCTION. MEASURES TO CONTROL EROSION AND OTHER POLLUTANTS SHALL IN PLACE BEFORE ANY TRENCHING WORK IS INITIATED. THESE MEASURES SHALL BE PROPERLY CONSTRUCTED AND MAINTAINED THROUGHOUT THE CONSTRUCTION PERIOD. PAYMENT FOR RESTORATION OF DRIVEWAYS, CURBS AND CUTTERS WILL NOT BE MADE DIRECTLY BUT SHALL BE INCLUDED IN THE CONTRACTOR'S BID PRICE IN THE VARIOUS ITEMS OF THE BID. RESTORATION OF PAPEMENT SHALL BE DONE WITH EQUIVALENT OR BETTER DULATIV MALERNIQS. THE COUNTRACTOR SHALL MATCH THE EXISTING THYONESS OR USE THE FOLLOWING MINIMALM HICKNESS MHICHERER IS GROUNTER. 8° MIN. BASI COURSE, 8° MIN. BASI COURSE, 2-1/2° MIN. ASPHALTIC CONNECTE THE COMPRAÇIOR SHALL RESIDER TO THER PORINAL OR BETTER COMPITION ALL IMPROVEMENTS. ANABOL N.S. RESULT OT THE COMSTRUCTION INCLUDING PARTHERS, CUIRES, SENSE, ENCADSCAPHIC CONSTRUCTIVES, UNIQUE PREVERS FOR THE SENSES FOR THE SENSES FOR THE SENSES FOR THE SENSES FOR THE PROPERTY OF ENSITING TIEMS SHALL BE INCIDENTAL TO AND INCLUDED WITH THE CONTRACTOR'S SED PARCE. DURING NON-WORKING HOURS, THE TRENCHES ON STREETS SHALL BE COVERED MITH NOWSKID STEEL PLATES AND ALL LANES MAINTAINED OPEN FOR TRAFFIC THE CONTRACTOR SHALL PROVIDE ACCESS TO AND FROM DRIVEWAY AND STREETS AT ALL TIMES EXCEPT AS NOTED ON THE PLANS. CONSTRUCTION NOTES This seek was proposed by pre-ci under my stativities, or "Subervision of predict and it can be considered as Chapter 115, New Manifest Home 1 (American Subervision of the Chapter Subervision and Landscape Architects, Subervision of Havard, Suberopier 1, Section 19-115-2. Definition effective Julie 19, 1939-1 **⑤** Earth Tech THE CONTRACTOR MAY ENCOUNTER MUNICIPAL SOLID WASTE OR ASH DIRNIG EXCAVATION. THE CONTRACTOR SHALL FOLICIAN PROCEDURES ESTABLISHED IN WASTE MANAGEMENTS OFFRATIONS PLANS FOR HANDLING THESE TYPES OF MATERIALS. MHFRE APPLICABLE AND FEASIBLE ALL EROSION & SEDIMENT CONTROL MEASURES TO CONTROL EROSION, SEDIMENT, AND OTHER POLLUTANTS SHALL BE IN PLACE BEFORE ANY EARTH MOVING PHASE OF THE CRADING IS INITIATED. TRENCHING OF PIPHOS SHALL HAVE A MINIMUM OF 6-INCHES OF A!" CROSSED AGREGATE ASSES BEDDING BEFORE PLACERUM OF PIPE ORGANIC MATERIAL AND COMPACTED TO A RELATIVE COMPACTION OF 95% WHEN PREVIOE TS WITHIN THE FELATIVE COMPACTION OF 95% WHEN PREVIOE TS WITHIN THE CONCECTE PUBBLE MASONEY SHALL CONDOM TO STATE OF HAWM STANDARD SECTION ROA MODTAR FOR BEDDING SHALL CONSIST OF DUE PART CREEKIN AND NOT MODE SHALL CONSIST OF DUE PART CREEKIN AND NOT MODE SHALL CONSIST OF MODERACEAST. HINDARIDE UNIT SHALL MOT EXCEED 2009 OF THE CENTRY OLMATITY SHALL NOT EXCEED 230 AN ADDITION TO AND NOT AS REPLACING ANY EXCENSIVE. ALL GROUTED ROCK RIP-RAP SHALL BE FULLY BEDDED IN MORTAR AND SO PLACED AS TO BREAK JOINTS AT LEAST 6-INCHES AND FORM A FIRM BOND. NO CONTRACION SHALL PERFORM ANY TERMONIC DEFERATIONS SO AS TO CAUSE FLUMOR DOCKS, SOIL OF CREENES TO FALL SOILE OF FLOW (NITO ADDINING PROPERIES, STREETS, OR NATURAL WATER CONSESS. SHOULD STORM HOW THE PROPERTY HOLDERED TORS ANY FRANCIAL ACTION BY THE CHEET ENGAGES. PUBLIC HEALTH SAFETY & MORTAR WHICH IS NOT USED WITHIN 30 MINUTES AFTER WATE HAS BEEN ADDED SHALL BE WASTED. RETEMPERING OF MORTAR SHALL NOT BE PERMITTED. MORTAR SHALL BE FRESHLY MIXED PREPARED AND LINIFORMUMED TO OBTAIN MINIMUM OF 3000 psi, 28-COMPRESSIVE STRENGTH, USE SUFFICIENT WATER CONSISTENT WITH SATISFACTORY WORKABILITY. ONITRACTOR SHALL PROPERTY DISPOSE OF ALL EXCAVAITED LANGELL WASTE BY RELOCATION TO WITHIN LANGELL WASTE BY RELOCATION TO WITHIN LANGELL WASTE BY RELOCATION TO WITHIN LANGELL WASTE AND LANGELL WASTE BY RELOCATION TO WITHOUT SUPPLY AND ANY AND ALL WORK TO PROJECT ALL PERSONNEL FROM ANY AND ALL WORK TO PROJECT ALL PERSONNEL FROM ANY AND ALL WASTE SUPPLY AND EXPOSED AND THAT SEEPACE AND EXPOSED THE PROPERTY WEIGHT. THE COMPACTOR AT HIS/HER OWN EYPENS SHALL KEEP THE PROMEST AND TIS SHEROWHOMS AREAS FREE FROM DIST NUSANCE. THE WORK SHALL BE IN CONFORMANCE WITH THE ARE POLLUTION STANDARDS AND REQULATIONS OF THE STATE DEPARTMENT OF THACHTH. CONVENIENCE NOTES CONSTRUCTION NOTES (CON'T THE CONTRACTOR SHALL DEVELOP HEALTH AND SAFETY PLAN PRIOR TO ANY CONSTRUCTION ACTIVITIES ASSOCIATED WITH THESE PLANS FOR WAIMANALO GULCH LANDFILL. THE CONTRACTOR SHALL PROVIDE, INSTALL AND MAINTAIN ALL NICESSARY SOINS LOHES, FLARES, BARRONDES, MARKERS, MARKERS, MARKERS, MARKERS, MARKERS, MARKERS, PRECMATIONS FOR THE PROTECTION, CONTENERVE AND SAFETY OF THE FUBLIC. THE CONTRACTOR SHALL OBSERVE AND COMPLY WITH ALL FEDERAL, STATE AND LOCAL LAWS REQUIRED FOR THE PROTECTION OF PUBLIC HEALTH, SAFETY AND ENVIRONMENTAL E COMPRAÇIOR SHALL BE RESPONSIBLE FOR THE PROPER PROSAL OF CHLORINATED WATER AND WATER USED FOR DROSTATIO TESTING TO SAFEQUARD PUBLIC HEALTH AND VIRONMENT IN ACCORDANCE WITH APPLICABLE DEPARTMENT -EEALTH REQUIREMENTS. 합 성 성 상 상 ES EES ELS. 묒몽붛돢돢퇉믁믁묨╸ CONTRACTOR HEICHT, HORIZONTAL HOSE BIBB HIGH DE WSITY POLYETHYLENE HAWAINAN ELECTRIC COMPANY HORIZONTAL HAWAINAN TELEPHONE COMPANY GALVANIZED BUARD POST, GUY POLE, GATE F GATE VALVE GUY MIRE DICTILE HOW, DRAIN INLET DICTILE HOW, PIPE DOUTILE HOW PIPE DRAIN MANHOLE DRAIN MANHOLE DRAINLEY OF PLANING AND PERMITING DEPARTIKEY OF PUBLIC MORKS DEPARTIKEY OF PUBLIC MORKS ASPHALTIC CONCRETE APPROXIMATE ASPHALT TREATED BASE INTERIM ON-SITE DRAINAGE MEASURES WAIMANALO GULCH LANDFILL EAST, EDGE ELECTRICAL ELECTRICAL ELECTRICAL OVERHEAD ELECTRICAL POLE EACH WAY EXISTING CENTERUNE CABLE TELENSION CARCH ELENSION CONCRETE CYLINDER PIPE COST PRON CHAINLING FENCE CLEMOLOT BOTTOW WALL BOARD OF WATER SUPPLY DRAIN, DIAMETER DETAIL COMENT RUBBLE MASONRY GENERAL & CONSTRUCTION NOTES CONCRETE CONNECT, CONNECTION CONSTRUCT CONTINUE, CONTINUATION LEAN OUT TO GRADE NOT FOR CONSTRUCTION **ABBREVIATIONS** THE PROPERTY OF THE PROPERTY O NATER RELATIVE COMPACTION RECONNECTION REMORGED REGUIRED REGUIRED ON CENTER DUTSIDE DIAMETER OVERHEAD OFFSET MILITY POLE PROPERTY LINE PAYEMENT POLYVINYL CHLORIDE MECHANICAL JOINT MONUMENT MEAN SEA LEVEL MT. WALVE BOX TELEPHONE TOP CURB THCK TAX WAP KEY TOP PIPE TOP WALL TYPICAL SEWER MANHOLE SPRINKLER SQUARE SEWER SLOPE OR SOUTH SEWER DRAIN MANHOLE SHEET CROSS WALK NORTH INEAR FEET NVERT PIPE THREAD IGHT-OF-WAY DATE: 10/19/05 SHEET 2 OF 16 G-2 DRAWING NO.